

超临界CO₂萃取专用泵性能参数表

型 号	额定流量L/h	进口压力MPa	出口压力MPa	进口管孔mm	出口管孔mm	电机功率kw
2J-X5/32-3.5	5	3.5	32	4	4	0.55
2J-X5/40-3.5	5	3.5	40	4	4	0.55
2J-X5/50-3.5	5	3.5	50	4	4	0.75
2J-XZ5/60-3.5	5	3.5	60	4	3	0.75
2J-XZ10/32-3.5	10	3.5	32	6	4	0.75
2J-XZ10/40-3.5	10	3.5	40	6	4	1.1
2J-XZ10/50-3.5	10	3.5	50	6	4	1.1
2J-XZ10/60-3.5	10	3.5	60	6	3	1.5
2J-XZ20/32-3.5	20	3.5	32	6	4	1.1
2J-XZ20/40-3.5	20	3.5	40	6	4	1.5
2J-XZ20/50-3.5	20	3.5	50	6	4	1.5
2J-XZ20/60-3.5	20	3.5	60	6	3	2.2
3DT-30/32-3.5	30	3.5	32	8	5	2.2
3DT-30/40-3.5	30	3.5	40	8	5	2.2
3DT-30/50-3.5	30	3.5	50	8	4	3
3DT-30/60-3.5	30	3.5	60	8	4	3
3DT-50/32-3.5	50	3.5	32	8	5	2.2
3DT-50/40-3.5	50	3.5	40	8	5	3
3DT-50/50-3.5	50	3.5	50	8	4	4
3DT-50/60-3.5	50	3.5	60	8	4	4
3DT-100/32-3.5	100	3.5	32	10	8	3
3DT-100/40-3.5	100	3.5	40	10	8	4
3DT-100/50-3.5	100	3.5	50	10	8	4
3DT-100/60-3.5	100	3.5	60	10	8	5.5
3DT-200/32-3.5	200	3.5	32	12	10	5.5
3DT-200/40-3.5	200	3.5	40	12	10	7.5
3DT-200/50-3.5	200	3.5	50	12	10	7.5
3DT-300/32-3.5	300	3.5	32	12	10	7.5
3DT-300/40-3.5	300	3.5	40	12	10	11
3DT-300/50-3.5	300	3.5	50	12	10	15
3DT-500/32-3.5	500	3.5	32	15	10	7.5
3DT-500/40-3.5	500	3.5	40	15	10	11
3DT-500/50-3.5	500	3.5	50	15	10	11
3DT-1000/32-3.5	1000	3.5	32	25	16	11
3DT-1000/40-3.5	1000	3.5	40	25	16	15
3DT-1000/50-3.5	1000	3.5	50	25	16	18.5
3DT-2000/25-3.5	2000	3.5	25	32	20	18.5
3DT-2000/32-3.5	2000	3.5	32	32	20	22
3DT-2000/40-3.5	2000	3.5	40	32	20	30